DTIC FILE COPY

(4)

CONTRACT REPORT BRL-CR-602

BRL

1938 – Serving the Army for Fifty Years – 1988

AD-A201 417

VALVE OPENING-TIME REQUIREMENTS FOR LB/TS

R. A. BERRY
G. D. LASSAHN
EG&G IDAHO, INC. (INEL)

NOVEMBER 1988

DTIC
ELECTE
S NOV 2 1 1988 D
H

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY

ABERDEEN PROVING GROUND, MARYLAND

88 11 21 015

DESTRUCTION NOTICE

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION: UNCLASSIFIED	1b. RESTRICTIVE MARKINGS: NONE
2a. SECURITY CLASSIFICATION AUTHORITY: N/A	3. DISTRIBUTION/AVAILABILITY OF REPORT: APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE: N/A	
4. PERFORMING ORGANIZATION REPORT NUMBER(S): EGG-PHY-8021	5. MONITORING ORGANIZATION REPORT NUMBER(S): BRL-CR-602
6a. NAME OF PERFORMING ORGANIZATION: E.G.&G. Idaho Inc. / 6b. OFFICE SYMBOL (If applicable):	7a. NAME OF MONITORING ORGANIZATION: U.S. Army Ballistic Research Laboratory
6c. ADDRESS (City, State, and ZIP Code): Idaho Falls, ID 83415	7b. ADDRESS (City, State, and ZIP Code): Aberdeen Proving Ground, MD 21005-5066
8a. NAME OF FUNDING/SPONSORING ORGANIZATION: U.S. Army BRL / 8b. OFFICE SYMBOL (If applicable): SLCBR-TB-B	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER: BRL-PO 76-87 (MIPR)
8c. ADDRESS (City, State, and ZIP Code): Aberdeen Proving Ground, MD 21005-5066	10. SOURCE OF FUNDING NUMBERS: PROGRAM ELEMENT NO. 62120 / PROJECT NO. AH25 / TASK NO. / WORK UNIT ACCESSION NO

11. TITLE (Include Security Classification)
VALVE OPENING TIME REQUIREMENTS FOR LB/TS

12. PERSONAL AUTHOR(S)
R. A. Berry and G. D. Lassahn

13a. TYPE OF REPORT	13b. TIME COVERED	14. DATE OF REPORT (Year, Month, Day)	15. PAGE COUNT
Final	FROM 87/09 TO 88/01	29 February 1988	130

16. SUPPLEMENTARY NOTATION

17. COSATI CODES		
FIELD	GROUP	SUB-GROUP
20	04	

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)
Computational ~~ID~~ Flow, Blast-Wave Simulation, Variable-Area Shock Tubes, Shock Formation, Rapid Opening Valves, Valve Opening Time.

19. ABSTRACT (Continue on reverse if necessary and identify by block number)
Computer calculations were performed to determine the maximum allowable valve opening times for producing sharply defined shocks of certain specifications ranging from 13.8 kPa to 241 kPa in the proposed Large Blast/Thermal Simulator for the U.S. Army Ballistic Research Laboratory. The maximum allowable valve opening times range from 63 milliseconds for the highest shock overpressure to 21 milliseconds for the lowest shock overpressure in the specified overpressure range.

20. DISTRIBUTION/AVAILABILITY OF ABSTRACT: ☒ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS	21 ABSTRACT SECURITY CLASSIFICATION: UNCLASSIFIED
22a. NAME OF RESPONSIBLE INDIVIDUAL: Mr. Klaus O. Opalka	22b TELEPHONE (Include Area Code): (301) 278-6036 / 22c. OFFICE SYMBOL: SLCBR-TB-B

DD Form 1473, JUN 86 *Previous editions are obsolete.* SECURITY CLASSIFICATION OF THIS PAGE

18. Subject Terms
Large Blast/Thermal Simulator (LB/TS)
Shock Tubes
Computational Fluid Dynamics

DTIC
COPY
INSPECTED
6

Accession For
NTIS GRA&I ☑
DTIC TAB ☐
Unannounced ☐
Justification
By
Distribution/
Availability Codes
Avail and/or
Dist Special
A-1

VALVE OPENING TIME REQUIREMENTS FOR LB/TS

R. A. Berry and G. D. Lassahn
Idaho National Engineering Laboratory
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, ID 83415

29 February 1988

Final Report

prepared for
U. S. Army Ballistic Research Laboratory
Aberdeen Proving Ground, Maryland 21005-5066

CONTENTS

1. INTRODUCTION	1
2. CALCULATIONS	2
3. RESULTS	6
4. CONCLUSIONS	12
REFERENCES	13

FIGURES

1. Diagram (not to scale) of shock tube, case 1 14
2. Pressure versus distance, case 1, zero opening time 15
3. Magnified pressure versus distance, case 1, zero opening time 16
4. Density versus distance, case 1, zero opening time 17
5. Magnified density versus distance, case 1, zero opening time 18
6. Velocity versus distance, case 1, zero opening time 19
7. Magnified velocity versus distance, case 1, zero opening time 20
8. Sound speed versus distance, case 1, zero opening time 21
9. Magnified sound speed versus distance, case 1, zero opening time 22
10. Shock front detail, pressure versus distance, case 1, zero opening time 23
11. Shock front detail, density versus distance, case 1, zero opening time 24
12. Shock front detail, velocity versus distance, case 1, zero opening time 25
13. Shock front detail, sound speed versus distance, case 1, zero opening time 26
14. Pressure versus time, case 1, zero opening time 27
15. Detail, pressure versus time, case 1, zero opening time 28
16. Pressure versus distance, case 1, 65ms opening time 29
17. Magnified pressure versus distance, case 1, 65ms opening time 30
18. Density versus distance, case 1, 65ms opening time 31
19. Magnified density versus distance, case 1, 65ms opening time 32
20. Velocity versus distance, case 1, 65ms opening time 33
21. Magnified velocity versus distance, case 1, 65ms opening time 34
22. Sound speed versus distance, case 1, 65ms opening time 35
23. Magnified sound speed versus distance, case 1, 65ms opening time 36
24. Shock front detail, pressure versus distance, case 1, 65ms opening time 37
25. Shock front detail, density versus distance, case 1, 65ms opening time 38
26. Shock front detail, velocity versus distance, case 1, 65ms opening time 39
27. Shock front detail, sound speed versus distance, case 1, 65ms opening time 40
28. Pressure versus time, case 1, 65ms opening time 41
29. Detail, pressure versus time, case 1, 65ms opening time 42
30. Pressure versus distance, case 8, zero opening time 43
31. Magnified pressure versus distance, case 8, zero opening time 44
32. Density versus distance, case 8, zero opening time 45
33. Magnified density versus distance, case 8, zero opening time 46
34. Velocity versus distance, case 8, zero opening time 47

35. Magnified velocity versus distance, case 8, zero opening time
36. Sound speed versus distance, case 8, zero opening time
37. Magnified sound speed versus distance, case 8, zero opening time
38. Pressure versus time, case 8, zero opening time
39. Detail, pressure versus time, case 8, zero opening time
40. Detail study, pressure versus distance, part 1
41. Detail study, pressure versus distance, part 2
42. Detail study, pressure versus distance, part 3
43. Detail study, magnified pressure versus distance, part 1
44. Detail study, magnified pressure versus distance, part 2
45. Detail study, magnified pressure versus distance, part 3
46. Detail study, density versus distance, part 1
47. Detail study, density versus distance, part 2
48. Detail study, density versus distance, part 3
49. Detail study, magnified density versus distance, part 1
50. Detail study, magnified density versus distance, part 2
51. Detail study, magnified density versus distance, part 3
52. Detail study, velocity versus distance, part 1
53. Detail study, velocity versus distance, part 2
54. Detail study, velocity versus distance, part 3
55. Detail study, magnified velocity versus distance, part 1
56. Detail study, magnified velocity versus distance, part 2
57. Detail study, magnified velocity versus distance, part 3
58. Detail study, sound speed versus distance, part 1
59. Detail study, sound speed versus distance, part 2
60. Detail study, sound speed versus distance, part 3
61. Detail study, magnified sound speed versus distance, part 1
62. Detail study, magnified sound speed versus distance, part 2
63. Detail study, magnified sound speed versus distance, part 3
64. Detail study, pressure versus distance 0.3 to 0.7, part 1
65. Detail study, pressure versus distance 0.3 to 0.7, part 2
66. Detail study, magnified pressure versus distance 0.3 to 0.7, part 1
67. Detail study, magnified pressure versus distance 0.3 to 0.7, part 2
68. Detail study, density versus distance 0.3 to 0.7, part 1
69. Detail study, density versus distance 0.3 to 0.7, part 2
70. Detail study, magnified density versus distance 0.3 to 0.7, part 1
71. Detail study, magnified density versus distance 0.3 to 0.7, part 2
72. Detail study, velocity versus distance 0.3 to 0.7, part 1
73. Detail study, velocity versus distance 0.3 to 0.7, part 2

74. Detail study, magnified velocity versus distance 0.3 to 0.7, part 1 87
75. Detail study, magnified velocity versus distance 0.3 to 0.7, part 2 88
76. Detail study, sound speed versus distance 0.3 to 0.7, part 1 89
77. Detail study, sound speed versus distance 0.3 to 0.7, part 2 90
78. Detail study, magnified sound speed versus distance 0.3 to 0.7, part 1 91
79. Detail study, magnified sound speed versus distance 0.3 to 0.7, part 2 92
80. Detail study, pressure versus distance 0.38 to 0.48 93
81. Detail study, density versus distance 0.38 to 0.48 94
82. Detail study, velocity versus distance 0.38 to 0.48 95
83. Detail study, sound speed versus distance 0.38 to 0.48 96
84. Detail study, pressure versus distance 0.39 to 0.43 97
85. Detail study, density versus distance 0.39 to 0.43 98
86. Detail study, velocity versus distance 0.39 to 0.43 99
87. Detail study, sound speed versus distance 0.39 to 0.43 100
88. Detail study, pressure versus time at -4 meters 101
89. Detail study, pressure versus time at -2 meters 102
90. Detail study, pressure versus time at 0 meters 103
91. Detail study, pressure versus time at 2 meters 104
92. Detail study, pressure versus time at 4 meters 105
93. Detail study, pressure versus magnified time 106
94. Detail study, characteristics plot 107
95. Pressure versus time, case 8, 20ms opening time 108
96. Pressure versus time, case 8, 30ms opening time 109
97. Pressure versus time, case 8, 50ms opening time 110
98. Pressure versus time, case 9, zero opening time 111
99. Pressure versus time, case 9, 20ms opening time 112
100. Pressure versus time, case 9, 30ms opening time 113
101. Pressure step versus valve opening time, cases 1, 2, and 3 114
102. Pressure step versus valve opening time, cases 4, 5, and 6 115
103. Pressure step versus valve opening time, cases 7, 8, and 9 116
104. Maximum allowable valve opening time versus driver pressure ratio 117
105. Driver temperature ratio versus driver pressure ratio 118

1. INTRODUCTION

The Ballistic Research Laboratory (BRL) of the U.S. Army is designing a Large Blast/Thermal Simulator (LB/TS), which is a proposed facility for creating pressure and thermal transients like those that occur near nuclear explosions.[1] The LB/TS is basically a large shock tube with area changes along its length. Unlike a conventional shock tube, which uses rupture diaphragms to separate the high pressure driver region from the low pressure driven region, it is desirable to utilize fast-opening valves in the LB/TS for wave shaping purposes as well as operational efficiency. However, with real valves, a finite opening time results in a compression wave with a finite rise time. The question then arises as to whether the compression wave will steepen to an adequate shock profile within the specified wave propagation distance, to simulate the desired blast wave. In support of this design effort, the Mathematical Analysis Unit at the Idaho National Engineering Laboratory (INEL) has done calculations to determine the maximum throat valve opening times allowable for the creation of certain shock waves in the LB/TS test section. Calculations were done for 9 specific cases specified by the BRL, representing 9 different initial conditions in the shock tube driver. All the calculations were done with the BRL-Q1D computer code[2]. This report summarizes the results of the valve opening calculations.

2. CALCULATIONS

For the present studies, the LB/TS was represented as shown in Figure 1 and described in Table 1. We are interested in the initial magnitude and rise time (not the later decay) of the shock at the test section 103.5 meters from the valve. The objective of the present study is to determine how fast the valve must open to allow the overpressure to rise from 5% to 95% of the plateau value in 0.5 milliseconds or less. We are not concerned with reflections from the end of the shock tube, which arrive too late to affect the shock front of interest. This allows us to model a shock tube substantially shorter than the real LB/TS, thereby saving some computer costs.

Calculations were done for the 9 cases listed in Table 2, representing different initial temperature and pressure conditions in the driver. Case 9 was different from the other 8 in that the shock tube geometry was a little different (see Table 1) and the valve was opened to a maximum of 43.75% instead of 100%.

The valve was represented as a parabolic constriction with a total length of 2 meters, located in the middle of the throat. The valve opening was represented as a linear function of time, from 0.1% open at time zero to 100% open (43.75% open for case 9) at the specified valve opening time. In addition to these calculations with the valve opening gradually, a reference calculation was done with the valve opened instantaneously for each case, to insure adequate resolution of the shock wave structure with the mesh used and, in some instances, to compare certain features of the wave structures.

Table 1: Shock Tube Geometry

	cases 1-6	cases 7-8	case 9
driver length	80.	20.	20.
driver diameter	5.490	5.490	5.440
converging nozzle length	2.	2.	2.
throat length	4.	4.	4.
throat diameter	2.743	2.743	1.8[illegible]
diverging nozzle length	4.	4.	4.
expansion tube length	110.	110.	110.
expansion tube diameter	14.494	14.494	14.494

(all dimensions are in meters)

TABLE 2: Calculation Results

case	pressure ratio	temperature ratio	nominal over-pressure [kPa]	reference over-pressure [kPa]	maximum valve opening time [second]
1	118.0	2.235	241.3	247.0	0.063
2	102.5	2.009	206.8	213.6	0.062
3	83.5	1.825	172.4	174.5	0.061
4	69.2	1.652	137.9	142.7	0.055
5	54.0	1.471	103.4	107.2	0.044
6	39.5	1.228	68.9	74.0	0.050
7	19.5	1.094	34.5	39.6	0.035
8	7.0	1.040	13.8	15.57	0.021
9	8.9	1.040	13.8	4.634	0.026

The calculations were done on INEL's CRAY X/MP-24 computer. Two minor modifications were made to the BRL-Q1D code: the sizes of the grid-dependent arrays were increased, and the plot and print output of time-dependent arrays was not started until the shock reached the first measurement station. For cases 8 and 9, the code was further modified by overlaying some large arrays, to decrease computer memory requirements and thereby improve computer access and turn-around time.

The BRL-Q1D code includes two options for the numerical method: the Beam-Warming and the MacCormack methods. For these calculations, the Beam-Warming method was used, with the BRL-recommended values of 1.0 for the Courant number and 0.04 for the smoothing coefficient. Preliminary estimates suggested that 10000 grid points would be adequate for these calculations, and this number was used successfully for cases 1-6. More grid points were required for cases 7-9.

3. RESULTS

The results for case 1 are given here in some detail; results for the other cases are given in much less detail, only as is necessary to describe significant differences from the results for case 1.

Figures 2-15 indicate the temporal and spatial dependence of some important variables calculated by the BRL-Q1D code for case 1 with the valve instantaneously opened 100%. In Figures 2-13, the horizontal axis is the normalized distance along the length of the shock tube. The actual total length corresponding to the normalized length of 1 is indicated by the value of L_{ref} (200 meters for case 1) printed at the top left corner of the page. The profile of the shock tube is indicated above the data plot, on the same horizontal scale as the data plot. The dependent variables plotted on the vertical scale in Figures 2-13 are also normalized to reference values as described in the BRL-Q1D code documentation.[2] The number printed just above the right end of each curve in Figures 2-13 is the time corresponding to that curve, in seconds. In Figures 10-13, the horizontal scale is expanded enough so that the individual points of the spatial grid are discernible, indicated by the vertical lines in the shock tube profile drawn above the graph proper. These graphs with high spatial resolution clearly indicate the spatial spread of the computed shock front, which is useful in evaluating the adequacy of the numerical method.

Figures 14 and 15 are graphs of overpressure (solid line) and dynamic pressure (dashed line) versus time, at the test location specified by the value listed for X-sta at the top of the page. The indicated distance of 97.5 meters from the beginning of the expansion tube corresponds to the required 103.5 meters from the center of the valve.

The data of most immediate interest is the overpressure versus time data indicated by the solid curves in Figures 14 and 15. This overpressure rises abruptly -- in a fraction of a millisecond -- when the shock arrives at the test location. At the top of this step is a small overshoot that is an artifact of the numerical procedures and is not indicative of a real phenomenon; the actual overpressure step is better indicated by extrapolating the almost-horizontal curve from the right of the step into the region of the step itself. This extrapolation procedure was used to estimate the overpressure step in all the studies reported here.

After the initial shock transient, the overpressure approaches a constant value, a plateau value, which is different for each of the 9 cases. This plateau value is used as the reference overpressure for each case.

Figures 16-29 illustrate the effect of the valve opening gradually instead of instantaneously. These figures represent a valve opening time of 65 milliseconds, which is close to the maximum allowable valve opening time for case 1. The major effect is to decrease the magnitude of the overpressure step and to increase the slope of the overpressure versus time curve after the initial shock. The rise time for the initial step is not noticeably changed by the gradual opening of the valve. Since the slope of the overpressure versus time curve after the initial shock is practically zero on a millisecond time scale, the acceptance criterion is essentially equivalent to the requirement that the magnitude of the overpressure step with the valve opened gradually be at least 95% of the reference overpressure. Thus, the procedure for estimating the maximum allowable valve opening time was to try different opening times and check whether the shock overpressure step was at least 95% of the reference value. (Of course the shock rise time was also checked for each run, to be sure that it was less than 0.5 ms.)

This case 1 description is representative of the results for cases 1-5. Case 6 and 7 gave results similar to those described for case 1, except that the overpressure decreased slightly instead of increasing after the initial shock for the calculations in which the valve was opened instantaneously. This difference was not important in estimating the maximum acceptable valve opening time.

Cases 8 and 9 gave qualitatively different results, as indicated in Figures 30-39 for case 8 with the valve instantaneously opened. In these cases, the initial shock was followed after a few milliseconds by a second shock that raised the overpressure to a value substantially higher than that of the first shock. The timing and magnitude of the second shock depend on the details of the geometry in the throat region of the shock tube. Figures 40-93 show some detailed plots for case 8 with the valve instantaneously opened, and Figure 94 shows an x-t plot for this case. The second shock moves a little faster that the first shock, but does not quite overtake the first shock in the 103.5 meter travel distance to the test station. It appeared that moving the valve closer to the end of the throat would decrease the initial delay between the first and second shocks and perhaps allow the second shock to overtake and merge with the first shock before they reached the test location. This change in the valve location was tried and found effective for this particular problem; unfortunately, this created another shock even later, so that the overall effect was not significantly changed.

The general conclusion drawn from this examination of case 8 is that the details of the shock tube geometry near the valve can cause irregular behavior of the overpressure versus time plot for the shock front, more complicated than the simple step followed by an almost flat region. In fact, this same irregular behavior occurs in all cases (note Figure 3), but in the higher pressure cases the irregular structure is merged into one simple shock before the shock reaches the measurement station.

Of course the simple shock tube geometry assumed here and the one-dimensional fluid flow calculation used here may not accurately represent the actual shock tube valve, throat, and nozzle behavior; nevertheless, it would not be surprising if phenomena qualitatively similar to the double shock behavior calculated for case 8 actually occurred in the real LB/TS. The question of immediate importance here is whether the model is realistic or informative enough to be useful, and whether (and how) to proceed with the studies of acceptable valve opening times for cases 8 and 9. The BRL personnel consulted[3] on this matter suggested prodeeding with the calculations, with the understanding that the results might not be taken at face value. Thus, the results presented here for cases 8 and 9 should be regarded as plausible but perhaps not very accurate estimates of the actual shock tube behavior. These results are a little sketchy, but more detailed studies did not seem warranted in view of the high cost and limited validity of computer calculations for the low-pressure cases like cases 8 and 9.

Overpressure versus time plots for cases 8 and 9 are shown in Figure 38 and Figures 95-100. The overpressure step associated with the first shock front appears to vary in a consistent manner with valve opening time, if the valve is opened gradually instead of instantaneously, and the results obtained from considering only this first shock front fit reasonably well with the results from cases 1-7. Therefore, despite the irregular nature of the overpressure versus time curve near the shock front, cases 8 and 9 were finally treated in the same manner as the other cases, with the overpressure step at the first shock front being considered the critical factor.

For the case 9 calculations with valve opening times of 20 and 30 milliseconds, the shock front rise time was a little greater than the required 0.5 milliseconds. However, previous experience indicates that the parameters of interest are not very sensitive to this factor, and the high calculation cost prohibited repeating these calculations with smaller step sizes to obtain the required rise time.

The results of these valve opening time studies are summarized in Figures 101-103, which indicate the magnitude of the shock overpressure step versus valve opening time for each of the 9 cases studied. Interpolation of these curves gives the maximum allowable valve opening time for each case, listed in Table 2 and graphed versus driver pressure to ambient pressure ratio in Figure 104. This curve does show a general trend, but it is not smooth. This lack of smoothness is at least partly attributed to the fact that the maximum allowable valve opening time is not a function of pressure ratio alone; it also depends on the temperature ratio, which is not a perfectly smooth function of the pressure ratio (see Figure 105) for the cases considered here.

4. CONCLUSIONS

The calculations done here indicate that the maximum allowable valve opening time is about 63 milliseconds for case 1, and somewhat less for the other, lower-pressure cases, as indicated in Table 2. The results for cases 1-7 are believed to be realistic; the results for cases 8 and 9 must be regarded with some skepticism. More reliable results would require a multidimensional computer model that is somewhat more complicated and substantially more expensive to run than the model used in this work.

REFERENCES

1. Opalka, K. O., "Large Blast-Wave Simulators (LBS) with Cold-Gas Drivers: Computational Design Studies", BRL-TR, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland 21005-5066.

2. Opalka, K. O. and Mark, A., "The BRL-Q1D Code: A Tool for the Numerical Simulation of Flows in Shock Tubes with Variable Cross-Sectional Areas", BRL-TR-2763, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland 21005-5066, October 1986.

3. Pearson, R. J. and Opalka, K. O., private communication, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland 21005-5066, January 1988.



Figure 1. Diagram (not to scale) of shock tube for Case 1.

pressure

CASE~ 1n: BRL1 - PLOT 1
Offset, Δy = 1.000

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940



Figure 2. Pressure versus distance, case 1, zero opening time

PLOT 2 19.09.16 WED 9 DEC, 1987 JOB=P1020846, ISSCO DISSPLA 10.0

pressure

CASE~ 1n: BRL1 – PLOT 1
Offset, Δy = 0.020

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940





Figure 3. Magnified pressure versus distance, case 1, zero opening time

PLOT 1 19.08.58 WED 9 DEC, 1987 JOB=P1020846, ISSCO DISSPLA 10.0

density

CASE~ 1n: 3PL1 PLOT 1
Offset, Δy = 0.100

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940





Figure 4. Density versus distance, case 1, zero opening time

density

CASE~ 1n: BRL1 – PLOT
Offset, Δy = 0.010

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.935, 0.938, 0.940



Figure 5. Magnified density versus distance, case 1, zero opening time

PLOT 3 19.09.30 WED 9 DEC, 1987 JOB=P1020846, ISSCO DISSPLA 10.0

velocity

CASE~ 1n: BRL1 – PLOT 1
Offset, Δy = 3.000

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940





Figure 6. Velocity versus distance, case 1, zero opening time

PLOT 4 19.10.05 WED 5 DEC, 1987 JOB#:ID20846, ISSCO DISSPLA 10.0

velocity

CASE~ 1r: redo 1n, check q01 – PLOT 1
Offset, Δy = 0.200

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940



Figure 7. Magnified velocity versus distance, case 1, zero opening time

PLOT 4 10.14.15 MON 11 JAN, 1988 JOB-P1050B9 , ISSCO DISSPLA 10.0

sound speed

CASE~ 1n: BRL1 – PLOT 1
Offset, Δy = 1.500

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940



Figure 8. Sound speed versus distance, case 1, zero opening time

sound speed

CASE~ 1r: redo 1n, check q01 – PLOT 1
Offset, Δy = 0.030

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.935, 0.939, 0.940



Figure 9. Magnified sound speed versus distance, case 1, zero opening time

PLOT 6 10.04.47 MON 11 JAN, 1988 JOB-PID5089 , ISSCO DISSPLA 10.0

pressure

CASE~ 1n: BRL1 – PLOT 3
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940





Figure 10. Shock front detail, pressure versus distance, case 1, zero opening time

PLOT 3 08.19.09 THUR 10 DEC, 1987 JOB=P1D30086, ISSCO DISSPLA 10.0

density

CASE~ 1n: BRL1 – PLOT 3
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.935, 0.938, 0.940





Figure 11. Shock front detail, density versus distance, case 1, zero opening time

PLOT 6 08.19.19 THUR 10 DEC, 1987 JOB-PID30086, ISSCO DISSPLA 10.0

velocity

CASE~ 1n: BRL1 - PLOT 3
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.935, 0.938, 0.940





Figure 12. Shock front detail, velocity versus distance, case 1, zero opening time

PLOT 9 08.19.29 THUR 10 DEC, 1987 JOB-P1030086, ISSCO DISPLA 10.0

sound speed

CASE~ 1n: BRL1 – PLOT 3
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1933. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.935, 0.938, 0.940





Figure 13. Shock front detail, sound speed versus distance, case 1, zero opening time

PLOT 12 08.19.40 THUR 10 DEC, 1987 JOB=P10300B6, ISSCO DISSPLA 10.0

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE: = 1n: BRL1			P-so	= 254.6 kPa	(36.92 psi)
L-ref = 200.0 m	X-sta	= 97.50 m	t-a	= 175.5 ms	
L-drv = 80.00 m	P-drv	= 118.0 atm	PPD	= 0.023 s	(0.083 s)
V-drv = 1933. m^3	P-amb	= 101.3 kPa	I-so	= 5.586 kPa-s	(0.171 kT)
L-dvn = 110.0 m	T-amb	= 288.2 K	Q-s	= 168.1 kPa	
L-rwe = 0.000 m	T4/T1	= 2.235	I-dyn	= 3.600 kPa-s	(0.287 kT)

PRESSURE-TIME HISTORY



Figure 14. Pressure versus time, case 1, zero opening time

PLOT 2 09.31.18 THUR 10 DEC, 1987 JOB-1053/542, ISSUE Display 10.0

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 1n: BRL1			P-so	= 254.6 kPa	(36.92 psi)
L-ref	= 200.0 m	X-sta	= 97.50 m	t-a	= 175.5 ms		
L-drv	= 80.00 m	P-drv	= 118.0 atm	PPD	= 0.023 s	(0.083 s)
V-drv	= 1933. m^3	P-amb	= 101.3 kPa	I-so	= 5.586 kPa-s	(0.171 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 168.1 kPa	
L-rwe	= 0.000 m	T4/T1	= 2.235	I-dyn	= 3.600 kPa-s	(0.287 kT)

PRESSURE-TIME HISTORY



Figure 15. Detail, pressure versus time, case 1, zero opening time

PLOT 2 09.34.58 THUR 10 DEC, 1987 JOB-PI038060, ISSCO DISSPLA 10.0

pressure

CASE~ 1u: BRL1 – PLOT 1
Offset, Δy = 1.000

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938

PRESSURE vs. DISTANCE



Figure 16. Pressure versus distance, case 1, 65ms opening time

PLOT 2 14.42.57 THUR 14 JAN, 1988 JOB-[illegible], ISSCO DISSPLA 10.0

pressure

CASE~ 1u: BRL1 – PLOT 1
Offset, Δy = 0.020

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938





Figure 17. Magnified pressure versus distance, case 1, 65ms opening time

PLOT 1 14.42.36 THUR 14 JAN, 1988 JOB-P1059900, ISSCO GISSPLR 10.0

density

CASE~ 1u; BRL1 – PLOT 1
Offset, Δy = 0.100

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938

DENSITY vs. DISTANCE



PLOT 4 14.43.39 THUR 14 JAN, 1988 JOB-F:359930, 15000 DISSPLA 10.0

Figure 18. Density versus distance, case 1, 65ms opening time

density

CASE~ 1u: BRL1 – PLOT 1
Offset, Δy = 0.010

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938



Figure 19. Magnified density versus distance, case 1, 65ms opening time

PLOT 3 14.43.14 THUR 14 JAN, 1988 JOB-P1059900, ISSCO DISSPLA 10.0

velocity

CASE~ 1u: BRL1 – PLOT 1
Offset, Δy = 3.000

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_i$ = 0.938





PLOT 6 14.44.16 THUR 14 JAN, 1988 JCB-PIDS9900, ISSCO DISSPLA 10.0

Figure 20. Velocity versus distance, case 1, 65ms opening time

velocity

CASE~ 1u: BRL1 – PLOT :
Offset, Δy = 0.200

L_{ref} = 200.0 m
$\forall_{drv}$ = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938



Figure 21. Magnified velocity versus distance, case 1, 65ms opening time

PLOT 5 14.43.57 THUR 14 JAN, 1988 JOB-P1059900, ISSCO DISSPLA 10.0

sound speed

CASE~ 1u: BRL1 - PLOT 1
Offset, Δy = 1.500

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938



Figure 22. Sound speed versus distance, case 1, 65ms opening time

PLOT 7 14.44.59 THUR 14 JAN, 1988 JOB-F1059900, ISSCO DISSPLA 10.0

sound speed

CASE~ 1u: BRL1 - PLOT 1
Offset, Δy = 0.030

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.635
$XSTA_1$ = 0.938

SOUND VELOCITY vs. DISTANCE



Figure 23. Magnified sound speed versus distance, case 1, 65ms opening time

PLOT 7 14.44.33 THUR 14 JAN, 1988 JOB-P1059900, ISSCO DISSPLA 10.0

pressure

CASE~ 1u: BRL1 – PLOT 1
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938



Figure 24. Shock front detail, pressure versus distance, case 1, 65ms opening time

PLOT 1 15.41.52 THUR 14 JAN, 1988 JOB-PID63148, ISSCO DISSPLA 10.0

density

CASE~ 1u: BRL1 – PLOT 1
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938



Figure 25. Shock front detail, density versus distance, case 1, 65ms opening time

PLOT 2 15.44.59 THUR 14 JAN, 1988 JOB-PID63148, ISSCO DISSPLA 10.0

velocity

CASE~ 1u: BRL1 – PLOT 1
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938





Figure 26. Shock front detail, velocity versus distance, case 1, 65ms opening time

PLOT 3 15.45.07 THUR 14 JAN, 1988 JOB-PID63148, ISSCO DISSPLA 10.0

sound speed

CASE~ 1u: BRL1 - PLOT 1
Offset, Δy = 0.000

L_{ref} = 200.0 m
V_{drv} = 1929. m^3
P_{41} = 118.0; T_{41} = 2.235
$XSTA_1$ = 0.938

SOUND VELOCITY vs. DISTANCE



Figure 27. Shock front detail, sound speed versus distance, case 1, 65ms opening time

PLOT 4 15.45.15 THUR 14 JAN, 1988 JOB-P1D63148, ISSCO DISSPLA 10.0

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 1u: BRL1			P-so	= 241.2 kPa	(34.98 psi)
L-ref	= 200.0 m	X-sta	= 97.50 m	t-a	= 204.8 ms	
L-drv	= 80.00 m	P-drv	= 118.0 atm	PPD	= 0.015 s	(0.054 s)
V-drv	= 1929. m^3	P-amb	= 101.3 kPa	I-so	= 3.502 kPa-s	(0.045 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 153.2 kPa	
L-rwc	= 0.000 m	T4/T1	= 2.235	I-dyn	= 2.224 kPa-s	(0.028 kT)

PRESSURE-TIME HISTORY



PLOT 1 15:10:56 THUR 14 JUN, 1990 JOB-P1061649, 15000 DISSPLA 10.2

Figure 28. Pressure versus time, case 1, 65ms opening time

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 1u: BRL1			P-so	= 241.2 kPa	(34.98 psi)
L-ref	= 200.0 m	X-sta	= 97.50 m	t-a	= 204.8 ms	
L-drv	= 80.00 m	P-drv	= 118.0 atm	PPD	= 0.015 s	(0.054 s)
V-drv	= 1929. m^3	P-amb	= 101.3 kPa	I-so	= 3.502 kPa-s	(0.045 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 153.2 kPa	
L-rwe	= 0.000 m	T4/T1	= 2.235	I-dyn	= 2.224 kPa-s	(0.082 kT)

PRESSURE–TIME HISTORY



PLOT 1 15.54.21 THUR 14 JAN, 1988 JOB-P1063612, ISSCO DISSPLA 10.0

Figure 29. Detail, pressure versus time, case 1, 65ms opening time

pressure

CASE~ 8q: BRL8 – PLOT 1
Offset, Δy = 1.000

L_{ref} = 140.0 m
V_{drv} = 512.9 m^3
P_{41} = 7.000; T_{41} = 1.040
$XSTA_i$ = 0.911



Figure 30. Pressure versus distance, case 8, zero opening time

PLOT 2 03.04.36 FRI 8 JAN, 1988 JOB=P1057385, ISSCO DISSPLA 10.0

pressure

CASE~ 8q: BRL8 – PLOT 1
Offset, Δy = 0.020

L_{ref} = 140.(m
V_{drv} = 512.(m^3
P_{41} = 7.000; T_{41} = 1.040
$XSTA_i$ = 0.911

PRESSURE vs. DISTANCE



Figure 31. Magnified pressure versus distance, case 8, zero opening time

PLOT 1 03.03.53 FRI 8 JAN, 1988 JOB-P1057385, ISSCO DISSPLA 10.0

density

CASE~ 8q: BRL8 PLOT 1
Offset, Δy = 0.100

L_{ref} = 140.0 m
V_{drv} = 512.9 m^3
P_{41} = 7.000; T_{41} = 1.040
$XSTA_i$ = 0.911

DENSITY vs. DISTANCE



Figure 32. Density versus distance, case 8, zero opening time

density

CASE~ 8q: BRL8 PLOT 1
Offset, Δy = 0.0 0.0

L_{ref} = 140.0 m
V_{drv} = 512.9 m^3
P_{41} = 7.000; T_{41} = 1.040
$XSTA_1$ = 0.911



DENSITY vs. DISTANCE



Figure 33. Magnified density versus distance, case 8, zero opening time

velocity

CASE~ 8q: BRL8 – PLOT 1
Offset, Δy = 3.000

L_{ref} = 140.0 m
V_{drv} = 512.9 m^3
P_{41} = 7.000; T_{41} = 1.040
$XSTA_i$ = 0.911



Figure 34. Velocity versus distance, case 8, zero opening time

velocity

CASE~ 8q: BRL8 - PLOT
Offset, Δy = 0.3

L_{ref} = 140.0 m
V_{drv} = 512.9 m^3
P_{41} = 7.000; T_{41} = 1.040
$XSTA_1$ = 0.911



VELOCITY vs. DISTANCE



Figure 35. Magnified velocity versus distance, case 8, zero opening time

PLOT 5 03.06.46 FRI 8 JAN, 1988 JOB#1057595, ISSCO DISSPLA 10.0

sound speed

CASE~ 8q: BRL8 -- PLOT 1
Offset, Δy = 1.500

L_{ref} = 140.0 m
V_{drv} = 512.9 m^3
P_{41} = 7.000; T_{41} = 1.040
$XSTA_i$ = 0.911



Figure 36. Sound speed versus distance, case 8, zero opening time

sound speed

CASE~ 8q: BRL8 - PLOT 1
Offset, Δy = 0.000

L_{ref} = 140.0 m
V_{drv} = 512.9 m^3
P_{41} = 7.000: T_{41} = 1.040
$XSTA_1$ = 0.911



Figure 37. Magnified sound speed versus distance, case 8, zero opening time

PLOT 7 03.08.19 FRI 8 JAN, 1988 JOB-P1057385, ISSCO DISSPLA 10.0

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8q: BRL8			P-so	= 11.96 kPa	(1.735 psi)
L-ref	= 140.0 m	X-sta	= 97.50 m	t-a	= 282.1 ms		
L-drv	= 20.00 m	P-drv	= 7.000 atm	PPD	= 0.083 s	(0.245 s)
V-drv	= 512.9 m^3	P-amb	= 101.3 kPa	I-so	= 1.209 kPa-s	(0.169 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 0.496 kPa	
L-rwe	= 0.000 m	T4/T1	= 1.040	I-dyn	= 0.078 kPa-s	(1.778 kT)

PRESSURE-TIME HISTORY



PLOT 1 08.22.79 FRI 8 JAN, 1988 JOB-F1061701, ISSCO DISSPLA 10.0

Figure 38. Pressure versus time, case 8, zero opening time

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE: = 8q: BRL8			P-so	= 11.98 kPa	(1.735 psi)
L-ref = 140.0 m	X-sta = 97.50 m		t-a	= 282.1 ms	
L-drv = 20.00 m	P-drv = 7.000 atm		PPD	= 0.063 s	(0.245 s)
V-drv = 512.9 m^3	P-amb = 101.3 kPa		I-so	= 1.209 kPa-s	(0.169 kT)
L-dvn = 110.0 m	T-amb = 288.2 K		Q-s	= 0.496 kPa	
L-rwe = 0.000 m	T4/T1 = 1.040		I-dyn	= 0.078 kPa-s	(1.778 kT)

PRESSURE-TIME HISTORY



Figure 39. Detail, pressure versus time, case 8, zero opening time

PLOT 1 08.32.24 FRI 8 JAN, 1988 JOB-P1061968, ISSCO DISSPLA 10.0

pressure

CASE~ 8h: BRL8 – PLOT 1
Offset, Δy = 1.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 40. Detail study, pressure versus distance, part 1

pressure

CASE~ 8h: BRL8 - PLOT 2
Offset, Δy = 1.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 41. Detail study, pressure versus distance, part 2

LOT 5 18.45.26 FRI 18 DEC, 1987 JOB=P1053500, [5500 DISPLA 16.0

pressure

CASE~ 8h: BRL8 - PLOT 3
Offset, Δy = 1.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_j$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 42. Detail study, pressure versus distance, part 3

pressure

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 0.020

L_{ref} = 40.00 m
V_{drv} = 278.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 43. Detail study, magnified pressure versus distance, part 1

18.44.30 FRI 18 DEC, 1987 JOB-P:D53500, ISSCO DISPLA 10.0

pressure

CASE~ 8h: BRL8 – PLOT 2
Offset, Δy = 0.020

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 44. Detail study, magnified pressure versus distance, part 2

pressure

CASE~ 8h: BRL8 – PLOT 3
Offset, Δy = 0.020

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 45. Detail study, magnified pressure versus distance, part 3

PLOT 4 18.44.55 FRI 18 DEC, 1987 JOB=P1053500, ISSCO DISSPLA 10.0

density

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 0.100

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 46. Detail study, density versus distance, part 1

density

CASE~ 8h: BRL8 - PLOT 2
Offset, $\Delta y = 0.100$

$L_{ref} = 40.00\ m$
$V_{drv} = 276.1\ m^3$
$P_{41} = 7.000$; $T_{41} = 1.000$
$XSTA_i = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700$



Figure 47. Detail study, density versus distance, part 2

density

CASE~ 8h: BRL8 -- PLOT 3
Offset, Δy = 0.100

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

DENSITY vs. DISTANCE



Figure 48. Detail study, density versus distance, part 3

density

CASE~ 8h: BRL8 – PLOT 1
Offset, Δy = 0.010

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 49. Detail study, magnified density versus distance, part 1

:ST 7 18.45.53 FRI 18 DEC, 1987 JOB=P1053500, ISSCO DISSPLA 10.0

density

CASE~ 8h: BRL8 – PLOT 2
Offset, Δy = 0.010

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_1$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 50. Detail study, magnified density versus distance, part 2

density

CASE~ 8h: BRL8 – PLOT 3
Offset, Δy = 0.010

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 51. Detail study, magnified density versus distance, part 3

PLOT 10 18.46.17 FRI 18 DEC, 1987 JOB-P1053500, ISSCO DISSPLA 10.0

velocity

CASE~ 8h: BRL8 – PLOT 1
Offset, Δy = 3.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 52. Detail study, velocity versus distance, part 1

velocity

CASE~ 8h: BRL8 - PLOT 2
Offset, Δy = 3.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 53. Detail study, velocity versus distance, part 2

LUT 17 18.48.19 FRI 18 DEC, 1987 JOB=PIDS3500, ISSCO DISSPLA 10.0

velocity

CASE~ 8h: BRL8 - PLOT 3
Offset, Δy = 3.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 54. Detail study, velocity versus distance, part 3

velocity

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 0.200

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



PLOT 13 18.47.18 FRI 18 DEC, 1987 JOB-#10053500, ISSCO DISSPLA 10.0

Figure 55. Detail study, magnified velocity versus distance, part 1

velocity

CASE~ 8h: BRL8 - PLOT 2
Offset, Δy = 0.200

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 56. Detail study, magnified velocity versus distance, part 2

velocity

CASE~ 8h: BRL8 – PLOT 3
Offset, Δy = 0.200

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{4i} = 7.000; T_{4i} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 57. Detail study, magnified velocity versus distance, part 3

sound speed

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 1.500

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 58. Detail study, sound speed versus distance, part 1

sound speed

CASE~ 8h: BRL8 – PLOT 2
Offset, Δy = 1.500

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 59. Detail study, sound speed versus distance, part 2

sound speed

CASE~ 8h: BRL8 - PLOT 3
Offset, Δy = 1.500

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 60. Detail study, sound speed versus distance, part 3

sound speed

CASE~ 8h: BRL8 - PLOT
Offset, Δy = 0.0

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{4i} = 7.000; Γ_{4i} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 61. Detail study, magnified sound speed versus distance, part 1

sound speed

CASE~ 8h: BRI.8 PLOT 2
Offset, Δy = 0.030

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 62. Detail study, magnified sound speed versus distance, part 2

sound speed

CASE~ 8h: BRL8 – PLOT 3
Offset, Δy = 0.030

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_j$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 63. Detail study, magnified sound speed versus distance, part 3

pressure

CASE~ 8h: BRL8 - PLOT
Offset, Δy = 1.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_1$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 64. Detail study, pressure versus distance 0.3 to 0.7, part 1

pressure

CASE~ 8h: BRL8 ~ PLOT
Offset, Δy = 1.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_j$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 65. Detail study, pressure versus distance 0.3 to 0.7, part 2

pressure

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 0.030

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

PRESSURE vs. DISTANCE



Figure 66. Detail study, magnified pressure versus distance 0.3 to 0.7, part 1

pressure

CASE~ 8h: BRL8 – PLOT 2
Offset, Δy = 0.020

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
$P_{\phi 1}$ = 7.000; $T_{\phi 1}$ = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

PRESSURE vs. DISTANCE



Figure 67. Detail study, magnified pressure versus distance 0.3 to 0.7, part 2

density

CASE~ 8h: BRL8 – PLOT 1
Offset, Δy = 0.100

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

DENSITY vs. DISTANCE



Figure 68. Detail study, density versus distance 0.3 to 0.7, part 1

density

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.560, 0.600, 0.700



Figure 69. Detail study, density versus distance 0.3 to 0.7, part 2

PLOT 9 19.40.36 MON 21 DEC, 1987 JOB-P1045985, ISSCO DISSPLA 10.0

density

CASE~ 8h: BRL8 -- PLOT 1
Offset, Δy = 0.010

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 70. Detail study, magnified density versus distance 0.3 to 0.7, part 1

density

CASE~ 8h: BRL8 - PL
Offset, Δy = 0.01

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 71. Detail study, magnified density versus distance 0.3 to 0.7, part 2

PLOT 7 .9.40.13 MON 21 DEC, 1987 JOB-P1045985, ISSCO DISSPLA 10.0

velocity

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 3.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 72. Detail study, velocity versus distance 0.3 to 0.7, part 1

velocity

CASE~ 8h: BRL8 – PLOT 2
Offset, Δy = 3.000

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_1$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 73. Detail study, velocity versus distance 0.3 to 0.7, part 2

PLOT 13 19.41.41 MON 21 DEC, 1987 JOB=PIC45985, ISSDG DISSPLA 10.0

velocity

CASE~ 8h: BRL8 PLOT 1
Offset, Δy = 0.200

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_j$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

VELOCITY vs. DISTANCE



Figure 74. Detail study, magnified velocity versus distance 0.3 to 0.7, part 1

velocity

CASE~ 8h: BRL8 ~ PLOT 2
Offset, $\Delta y = 0.200$

$L_{ref} = 40.00\ m$
$V_{drv} = 276.1\ m^3$
$P_{41} = 7.000$; $T_{41} = 1.000$
$XSTA_1 = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700$



Figure 75. Detail study, magnified velocity versus distance 0.3 to 0.7, part 2

sound speed

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 1.500

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 76. Detail study, sound speed versus distance 0.3 to 0.7, part 1

RUN 15 19.41.55 MON 21 DEC, 1987 JOB=[U45585,15500] DISPLA 10.0

sound speed

CASE~ 8h: BRL8 – PLOT 2
Offset, Δy = 1.500

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700





Figure 77. Detail study, sound speed versus distance 0.3 to 0.7, part 2

sound speed

CASE~ 8h: BRL8 – PLOT 1
Offset, Δy = 0.030

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

SOUND VELOCITY vs. DISTANCE



Figure 78. Detail study, magnified sound speed versus distance 0.3 to 0.7, part 1

sound speed

CASE~ 8h: BRL8 -- PLOT
Offset, Δy = 0.00

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700





Figure 79. Detail study, magnified sound speed versus distance 0.3 to 0.7, part 2

pressure

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 0.020

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 80. Detail study, pressure versus distance 0.38 to 0.48

density

CASE~ 8h: BRL8 – PLOT 1
Offset, Δy = 0.010

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 81. Detail study, density versus distance 0.38 to 0.48

PLOT 3 09.18.49 WED 23 DEC, 1987 JOB-P1029095, ISSCO DISSPLA 10.0

velocity

CASE~ 8h: BRL8 PLOT 1
Offset, Δy = 0.200

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

VELOCITY vs. DISTANCE



Figure 82. Detail study, velocity versus distance 0.38 to 0.48

sound speed

CASE~ 8h: BRL8 – PLOT
Offset, Δy = 0.0

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 83. Detail study, sound speed versus distance 0.38 to 0.48

pressure

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 0.020

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700

PRESSURE vs. DISTANCE



Figure 84. Detail study, pressure versus distance 0.39 to 0.43

density

CASE~ 8h: BRL8 -- PLOT
Offset, Δy = 0.010

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 85. Detail study, density versus distance 0.39 to 0.43

PLOT 3 09.34.17 WED 23 DEC, 1987 JOB-PID30123, ISSCO DISSPLA 10.0

velocity

CASE~ 8h: BRL8 - PLOT 1
Offset, Δy = 0.200

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 86. Detail study, velocity versus distance 0.39 to 0.43

sound speed

CASE~ 8h: BRL8 – PLOT
Offset, Δy = 0.0

L_{ref} = 40.00 m
V_{drv} = 276.1 m^3
P_{41} = 7.000; T_{41} = 1.000
$XSTA_i$ = 0.400, 0.450, 0.500, 0.550, 0.600, 0.700



Figure 87. Detail study, sound speed versus distance 0.39 to 0.43

PLOT 7 09.34.49 WED 23 DEC, 1987 JOB=1035123, ISSCO DISPLAY 16.3

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8h: BRL8			P-so	= 142.1 kPa	(20.60 ps
L-ref	= 40.00 m	X-sta	= -4.000 m	t-a	= 3.906 ms		
L-drv	= 10.00 m	P-drv	= 7.000 atm	PPD	= 0.030 s	(0.076 s
V-drv	= 276.1 m^3	P-amb	= 101.3 kPa	I-so	= 3.174 kPa-s	(0.057 k
L-dvn	= 20.00 m	T-amb	= 288.2 K	Q-s	= 114.0 kPa		
L-rwe	= 0.000 m	T4/T1	= 1.000	I-dyn	= 5.457 kPa-s	(8.724 k

PRESSURE-TIME HISTORY



Figure 88. Detail study, pressure versus time at -4 meters

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8h: BRL8			P-so	[illegible]
L-ref	= 40.00 m	X-sta	= -2.000 m	t-a	[illegible]
L-drv	= 10.00 m	P-drv	= 7.000 atm	PPD	[illegible]
V-drv	= 276.1 m^3	P-amb	= 101.3 kPa	I-so	[illegible]
L-dvn	= 20.00 m	T-amb	= 288.2 K	Q-s	[illegible]
L-rwe	= 0.000 m	T4/T1	= 1.000	I-dyn	[illegible]

PRESSURE-TIME HISTORY



PLOT 2 18.34.40 MON 21 DEC, 1987 JOB-P1044795, ISSCO DISSPLA 10.0

Figure 89. Detail study, pressure versus time at -2

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8h: BRL8			P-so	= 28.39 kPa (4.117 psi)
L-ref	= 40.00 m	X-sta	= 0.000 m	t-a	= 13.58 ms
L-drv	= 10.00 m	P-drv	= 7.000 atm	PPD	= 0.020 s (0.029 s)
V-drv	= 276.1 m^3	P-amb	= 101.3 kPa	I-so	= 0.302 kPa-s (0.000 kT)
L-dvn	= 20.00 m	T-amb	= 288.2 K	Q-s	= 2.733 kPa
L-rwe	= 0.000 m	T4/T1	= 1.000	I-dyn	= 0.017 kPa-s (0.000 kT)

PRESSURE-TIME HISTORY



Figure 90. Detail study, pressure versus time at 0 meters

PLOT 3 18.34.42 MON 21 DEC, 1987 Job-r1u44795, ISSCO DISSPLA 10.0

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8h: BRL8			P-so	= 26.79 kPa
L-ref	= 40.00 m	X-sta	= 2.000 m	t-a	= 18.38 ms
L-drv	= 10.00 m	P-drv	= 7.000 atm	PPD	= 0.015 s
V-drv	= 276.1 m^3	P-amb	= 101.3 kPa	I-so	= 0.215 kPa s
L-dvn	= 20.00 m	T-amb	= 288.2 K	Q-s	= 2.483 kPa
L-rwe	= 0.000 m	T4/T1	= 1.000	I-dyn	= 0.902 kPa

PRESSURE–TIME HISTORY



PLOT 4 18.34.44 MON 21 DEC, 1987 JOB-P1D44795, ISSCO DISSPLA 10.0

Figure 91. Detail study, pressure versus time at 2 meters

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8h: BRL8			P-so	= 25.56 kPa	(3.708 psi)
L-ref	= 40.00 m	X-sta	= 4.000 m	t-a	= 24.17 ms	
L-drv	= 10.00 m	P-drv	= 7.000 atm	PPD	= 0.009 s	(0.015 s)
V-drv	= 276.1 m^3	P-amb	= 101.3 kPa	I-so	= 0.150 kPa-s	(0.000 kT)
L-dvn	= 20.00 m	T-amb	= 288.2 K	Q-s	= 2.223 kPa	
L-rwe	= 0.000 m	T4/T1	= 1.000	I-dyn	= 0.009 kPa-s	(0.000 kT)

PRESSURE-TIME HISTORY



Figure 92. Detail study, pressure versus time at 4 meters

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8h: BRL8			P-so	= 25.56 kPa
L-ref	= 40.00 m	X-sta	= 4.000 m	t-a	= 31.17 ms
L-drv	= 10.00 m	P-drv	= 7.000 atm	PPD	= 0.000
V-drv	= 276.1 m^3	P-amb	= 101.3 kPa	I-so	= 0.150 kPa
L-dvn	= 20.00 m	T-amb	= 288.2 K	Q-s	= 2.323 kPa
L-rwe	= 0.000 m	T4/T1	= 1.000	I-dyn	= 0.000 kPa

PRESSURE-TIME HISTORY



Figure 93. Detail study, pressure versus magnified time

PLOT 5 18.47.03 MON 21 DEC, 1987 JOB=7.044974, 13500 D155PLR 10.0



Figure 94. Detail study, characteristics plot

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8s: BRL8			P-so	[illegible]
L-ref	= 140.0 m	X-sta	= 97.50 m	t-a	[illegible]
L-drv	= 30.00 m	P-drv	= 7.000 atm	PPD	[illegible]
V-drv	= 508.2 m^3	P-amb	= 101.3 kPa	I-so	[illegible]
L-dyn	= 110.0 m	T-amb	= 288.2 K	Q-s	[illegible]
L-rwe	= 0.000 m	T4/T1	= 1.040	I-dyn	[illegible]

PRESSURE–TIME HISTORY



Figure 95. Pressure versus time, case 8, 20ms opening time

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8t: BRL8			P-so	= 12.98	kPa	(1.882 psi)
L-ref	= 140.0 m	X-sta	= 97.50 m	t-a	= 290.6	ms	
L-drv	= 30.00 m	P-drv	= 7.000 atm	PPD	= 0.026	s	(0.026 s)
V-drv	= 508.2 m^3	P-amb	= 101.3 kPa	I-so	= 0.362	kPa-s	(0.004 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 0.583	kPa	
L-rwe	= 0.000 m	T4/T1	= 1.040	I-dyn	= 0.018	kPa-s	(0.014 kT)

PRESSURE-TIME HISTORY



Figure 96. Pressure versus time, case 8, 30ms opening time

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 8r: BRL8			P-so	= 10.31 kPa	(1.495 psi
L-ref	= 140.0 m	X-sta	= 97.50 m	t-a	= 294.6 ms	
L-drv	= 20.00 m	P-drv	= 7.000 atm	PPD	= 0.067 s	(0.212 s
V-drv	= 508.2 m^3	P-amb	= 101.3 kPa	I-so	= 0.915 kPa-s	(0.098 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 0.369 kPa	
L-rwe	= 0.000 m	T4/T1	= 1.040	I-dyn	= 0.045 kPa-s	(0.725 kT)

PRESSURE-TIME HISTORY



PLOT 1 12.47.18 FRI 8 JAN, 1988 JOB-P1076025, 15500 DISPLAY 10.0

Figure 97. Pressure versus time, case 8, 50ms opening time

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 91: BRL9			P-so	= 6.508 kPa (0.944 psi
L-ref	= 140.0 m	X-sta	= 97.50 m	t-a	= 291.0 ms
L-drv	= 20.00 m	P-drv	= 8.900 atm	PPD	= 0.036 s (0.061 s)
V-drv	= 491.4 m^3	P-amb	= 101.3 kPa	I-so	= 0.175 kPa-s (0.002 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 0.300 kPa
L-rwe	= 0.000 m	T4/T1	= 1.040	I-dyn	= 0.003 kPa-s (0.002 kT)

PRESSURE-TIME HISTORY



PLOT 1 08.33.07 THUR 7 JAN, 1988 JOB=P1016919, ISSCO DISSPLA 10.0

Figure 98. Pressure versus time, case 9, zero opening time

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 9s: BRL9			P-so	= 4.334 kPa
L-ref	= 140.0 m	X-sta	= 97.50 m	t-a	= 299.3 m/s
L-drv	= 20.00 m	P-drv	= 8.900 atm	PPD	= 0.065 s
V-drv	= 490.4 m^3	P-amb	= 101.3 kPa	I-so	= 0.296 kPa
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 0.300 kPa
L-rwe	= 0.000 m	T4/T1	= 1.040	I-dyn	= 0.005 kPa

PRESSURE-TIME HISTORY



Figure 99. Pressure versus time, case 9, 20ms opening time

SHOCK TUBE WITH CONICAL DRIVER AND NOZZLE

CASE:	= 9r: BRL9			P-so	= 5.022	kPa	(0.728 psi)
L-ref	= 140.0 m	X-sta	= 97.50 m	t-a	= 297.6	ms	
L-drv	= 30.00 m	P-drv	= 8.900 atm	PPD	= 0.029	s	(0.032 s)
V-drv	= 490.4 m^3	P-amb	= 101.3 kPa	I-so	= 0.140	kPa-s	(0.001 kT)
L-dvn	= 110.0 m	T-amb	= 288.2 K	Q-s	= 0.300	kPa	
L-rwe	= 0.000 m	T4/T1	= 1.040	I-dyn	= 0.002	kPa-s	(0.003 kT)

PRESSURE-TIME HISTORY



Figure 100. Pressure versus time, case 9, 30ms opening time



Figure 101. Pressure step versus valve opening time, cases 1, 2, and 3



Figure 102. Pressure step versus valve opening time, cases 4, 5, and 6



Figure 103. Pressure step versus valve opening time, cases 7, 8, and 9



Figure 104. Maximum allowable valve opening time versus driver pressure ratio



Figure 105. Driver temperature ratio versus driver pressure ratio

DISTRIBUTION LIST

No. of Copies	Organization
12	Administrator Defense Technical Info Center ATTN: DTIC-FDAC Cameron Station, Bldg 5 Alexandria, VA 22304-6145
1	Director of Defense Research & Engineering ATTN: DD/TWP Washington, DC 20301
1	Asst. to the Secretary of Defense (Atomic Energy) ATTN: Document Control Washington, DC 20301
2	Deputy Chief of Staff for Operations and Plans ATTN: Technical Library Director of Chemical and Nuclear Operations Department of the Army Washington, DC 20310
1	Director Defense Advanced Research Projects Agency ATTN: Tech Lib 1400 Wilson Boulevard Arlington, VA 22209
2	Director Federal Emergency Management Agency ATTN: D. A. Bettge Technical Library Washington, DC 20472
1	Director Defense Intelligence Agency ATTN: DT-2/Wpns & Sys Div Washington, DC 20301
1	Director National Security Agency ATTN: E. F. Butala, R15 Ft. George G. Meade, MD 20755
1	Director Joint Strategic Target Planning Staff JCS Offut AFB Omaha, NB 68113
5	Director Defense Nuclear Agency ATTN: CSTI (Tech Lib) DFSP (G. Ullrich) NANS SPSD (Goering/Rohr) TDTR (Kennedy/Hrinishin) Washington, DC 20305
2	Commander Field Command, DNA ATTN: FCPR FCTMOF Kirtland AFB, NM 87115
1	Commander Field Command, DNA Livermore Branch ATTN: FCPRL P.O. Box 808 Livermore, CA 94550
1	HQDA DAMA-ART-M Washington, DC 20310
10	Central Intelligence Agency DIR/DB/Standard ATTN: GE-47 HQ Washington, DC 20505
1	Commander US Army Strategic Defense Command ATTN: CSSD-H-MPL (Tech Lib) CSSD-H-XM (Dr. Davies) P.O. Box 1500 Huntsville, AL 35807
1	Commander US Army Engineer Division ATTN: HNDED-FD P.O. Box 1500 Huntsville, AL 35807

DISTRIBUTION LIST

No. of Copies	Organization
3	Commander US Army Engineers Waterways Experiment Station ATTN: Technical Library Jim Watt Jim Ingram P.O. Box 631 Vicksburg, MS 39180-0631
2	Commander US Army Materiel Command ATTN: AMCDRA-ST John Shea 5001 Eisenhower Avenue Alexandria, VA 22333-0001
3	Commander US Army Armament RD&E Center ATTN: SMCAR-TDC SMCAR-MSI SMCAR-TSS Dover, NJ 07801-5001
1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-7300
1	Commander US AMCCOM ARDEC CCAC Benet Weapons Laboratory ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050
1	Commander US Army Aviation Systems Command ATTN: AMSAV-ES 4300 Goodfellow Boulevard St. Louis, MO 63120-1798
1	Director US Army Aviation Research and Technology Activity Ames Research Center Moffett Field, CA 94035-1099
3	Commander US Army Communications & Electronics Command (CECOM) HQ ATTN: AMSEL-RD AMSEL-IM-L AMSEL-RO-TPPO-P Fort Monmouth, NJ 07703-5301
3	Director US Army Harry Diamond Labs SLCHD-NW-RA (L. Belliveau) SLCHD-NW-P (Gwaltney/Meszaros) SLCHD-TA-L (Tech Lib) 2800 Powder Mill Road Adelphi, MD 20783-1197
1	Commander US Army Missile Command ATTN: AMSMI-RD Redstone Arsenal, AL 35898-5245
1	Director US Army Missile and Space Intelligence Center ATTN: AIAMS-YDL Redstone Arsenal, AL 35898-5500
2	Commander US Army Natick Research and Development Center ATTN: AMDNA-D (Dr. D. Sieling) STRNC-UE (J. Calligeros) Natick, MA 01762
1	Commander US Army Tank Automotive Command ATTN: AMSTA-TSL Warren, MI 48397-5000
1	Commander US Army Foreign Science and Technology Center ATTN: Research & Data Branch 220 7th Street . NE. Charlottesville, VA 22901

DISTRIBUTION LIST

No. of Copies	Organization
1	Commander US Army Logistics Management Center ATTN: ATCL-O (R. Cameron) Fort Lee, VA 23801
2	Commander US Army Materials Technology Laboratory ATTN: AMXMR-ATL Eugene de Luca Watertown, MA 02172-0001
1	Commander US Army Research Office ATTN: SLCRO-D P.O. Box 12211 Research Triangle Park, NC 27709-2211
3	Commander US Army Nuclear & Chemical Agency ATTN: ACTA-NAW MONA-WE Tech. Lib. 7500 Backlick Rd, Bldg. 2073 Springfield, VA 22150
1	Commander US Army TRADOC ATTN: DCST&E Fort Monroe, VA 23651-5143
1	Commander US Army Test & Evaluation Command Nuclear Effects Laboratory ATTN: STEWS-TE-NO (Dr. J. L. Meason) P.O. Box 477 White Sands Missile Range, NM 88002-
2	Director US Army TRADOC Analysis Command (WSML) ATTN: LTC John Hesse ATOR-TSL White Sands Missile Range, NM 88002-5502
2	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5400
1	Commander US Army Development & Employment Agency ATTN: MODE-ORO Fort Lewis, WA 98433-5000
1	Commandant Interservice Nuclear Weapons School ATTN: Technical Library Kirtland AFB, NM 87115
2	Chief of Naval Operations ATTN: OP-03EG OP-985F Department of the Navy Washington, DC 20350
1	Chief of Naval Research ATTN: N. Perrone Department of the Navy Arlington, VA 22217
1	Director Strategic Systems Projects Office ATTN: NSP-43, Tech Library Department of the Navy Washington, DC 20360
1	Commander Naval Electronic Systems Command ATTN: PME 117-21A Washington, DC 20360
1	Commander Naval Facilities Engineering Command Washington, DC 20360
1	Commander Naval Sea Systems Command ATTN: Code SEA-62R Department of the Navy Washington, DC 20362-5101

DISTRIBUTION LIST

No. of Copies	Organization
3	Officer-in-Charge (Code L31) Naval Construction Battalion Center Civil Engineering Laboratory ATTN: Stan Takahashi R. J. Odello Technical Library Port Hueneme, CA 93041
1	Commander David W. Taylor Naval Ship Research & Development Command ATTN: Lib Div, Code 522 Bethesda, MD 20084-5000
1	Commander Naval Surface Weapons Center ATTN: DX-21, Library Dahlgren, VA 22448-5000
2	Commander Naval Surface Weapons Center ATTN: Code WA501, Navy Nuclear Programs Office Code WX21, Tech Library Silver Spring, MD 20902-5000
1	Commander Naval Weapons Center ATTN: Code 533, Tech Library China Lake, CA 93555-6001
1	Commander Naval Weapons Evaluation Fac ATTN: Document Control Kirtland AFB, NM 87117
1	Commander Naval Research Laboratory ATTN: Code 2027, Tech Library Washington, DC 20375
1	Superintendent Naval Postgraduate School ATTN: Code 2124, Tech Library Monterey, CA 93940
1	AFSC/SDOA Andrews AFB, MD 20334

No. of Copies	Organization
2	Air Force Armament Technology Laboratory ATTN: AFATL/DOIL AFATL/DLYV Eglin AFB, FL 32542-5438
1	AFESC/RDCS ATTN: Paul Rosengren Tyndall AFB, FL 32403
1	RADC (EMTLD/Docu Library) Griffiss AFB, NY 13441
3	Air Force Weapons Laboratory ATTN: SUL NTES, R. Henny NTED, J. W. Aubrey Kirtland AFB, NM 87117-6008
2	Commander-in-Chief Strategic Air Command ATTN: NRI-STINFO Lib Offutt AFB, NB 68113
1	AFIT (Lib Bldg. 640, Area B) Wright-Patterson AFB, OH 45433
1	FTD/NIIS Wright-Patterson AFB Ohio 45433
1	U.S. Department of Energy Idaho Operations Office ATTN: Spec Programs (J. Patton) 785 DOE Place Idaho Falls, ID 83402
2	Director Idaho National Engineering Laboratory EG&G Idaho Inc. ATTN: Dr. R. A. Berry Mr. W. C. Reed P.O. Box 1625 Idaho Falls, ID 83415
1	Director Lawrence Livermore Lab ATTN: Tech Info Dept L-3 P.O. Box 808 Livermore, CA 94550

DISTRIBUTION LIST

No. of Copies	Organization
2	Director Los Alamos Scientific Lab. ATTN: Doc Control for Rpts Library P.O. Box 1663 Los Alamos, NM 87544
2	Director Sandia Laboratories ATTN: Doc Control 3141 Sandia Rpt Collection L. J. Vortman P.O. Box 5800 Albuquerque, NM 87185-5800
1	Director Sandia Laboratories Livermore Laboratory ATTN: Doc Control for Tech Library P.O. Box 969 Livermore, CA 94550
1	Director National Aeronautics and Space Administration Scientific & Tech Info Fac P.O. Box 8757, BWI Airport Baltimore, MD 21240
1	Director NASA-Ames Research Center Applied Computational Aerodynamics Branch ATTN: MS 202-14, Dr. T. Holtz Moffett Field, CA 94035
3	Aberdeen Research Center ATTN: N.H. Ethridge J. Keefer Library P.O. Box 548 Aberdeen, MD 21001
1	Applied Research Associates, Inc. ATTN: R. L. Guice 7114 West Jefferson Ave., Suite 305 Lakewood, CO 80235
1	Black & Veach Consulting Engineers ATTN: H. D. Laverentz 1500 Meadow Lake Parkway Kansas City, MO 64114
1	The Boeing Company ATTN: Aerospace Library P.O. Box 3707 Seattle, WA 98124
1	Carpenter Research Corporation ATTN: H. Jerry Carpenter Suite 424 904 Silver Spur Road Rolling Hills Estates, CA 90274
1	Dynamics Technology, Inc. ATTN: D. T. Hove Suite 300 21311 Hawthorne Blvd. Torrance, CA 90503
1	EATON Corporation Defense Valve & Actuator Div. ATTN: Dr. J. Y. S. Yang 2338 Alaska Ave. El Segundo, CA 90245-4896
4	Kaman AviDyne ATTN: Dr. R. Reutenick (2 cys) Mr. S. Criscione Mr. R. Milligan 83 Second Avenue Northwest Industrial Park Burlington, MA 01830
2	Kaman Sciences Corporation ATTN: Dr. F. W. Balicki Tech Lib 1613 University Blvd. N.E. Albuquerque, NM 87102
2	Kaman-TEMPO ATTN: DASIAC Don Sachs P.O. Drawer QQ 816 State Street Santa Barbara, CA 93102

DISTRIBUTION LIST

No. of Copies	Organization
1	New Mexico Engineering Research Institute (CERF) University of New Mexico ATTN: Dr. J. Leigh P.O. Box 25 Albuquerque, NM 87131
2	R&D Associates ATTN: Technical Library Allan Kuhl P.O. Box 9695 Marina Del Rey, CA 90291
1	R&D Associates ATTN: G.P. Ganong P.O. Box 9330 Albuquerque, NM 87119
1	Science Applications International Corp. ATTN: Mr. J. Guest 4615 Hawkins Blvd. N.E. Albuquerque, NM 87109
1	Science Applications Internationak Corp. ATTN: Technical Library 1250 Prospect Plaza La Jolla, CA 92037
1	Sparta, Inc. ATTN: I. B. Osofsky Suite 250, 23293 So. Pointe Dr. Laguna Hills, CA 92653
1	Sverdrup Technology, Inc. ATTN: R. F. Starr P. O. Box 884 Tullahoma, TN 37388
2	Systems, Science and Software ATTN: C. E. Needham Lynn Kennedy PO Box 8243 Albuquerque, NM 87198
1	AFELM, The Rand Corporation ATTN: Library-D 1700 Mainm Street Santa Monica, CA 90406

No. of Copies	Organization
1	Battelle Memorial Institute ATTN: Technical Library 505 King Avenue Columbus, OH 43201
1	California Institute of Technology ATTN: Tech Lib 1201 E. California Blvd. Pasadena, CA 91109
1	Massachusetts Institute of Technology ATTN: Technical Library Cambridge, MA 02139
1	Northrop University ATTN: Dr. F. B. Safford 5800 W. Arbor Vitae St. Los Angeles, CA 90045
2	Southwest Research Institute ATTN: Dr. W. E. Baker A. B. Wenzel 8500 Culebra Road San Antonio, TX 78228

Aberdeen Proving Ground

Dir, USAMSAA
ATTN: AMXSY-D
AMXSY-MP (H. Cohen)

Cdr, USATECOM
ATTN: AMSTE-SI-F
AMSTE-TE-F (L. Tokarski)

Cdr, CRDEC
ATTN: SMCCR-RSP-A
SMCCR-MU
SMCCR-SPS-IL

Cdr, USATHMA
ATTN: AMXTH-TE

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number_____ Date of Report_____

2. Date Report Received_____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.)_____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.)_____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate._____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.)

CURRENT ADDRESS

Name

Organization

Address

City, State, Zip

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD ADDRESS

Name

Organization

Address

City, State, Zip

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

— — — — — — — — — — FOLD HERE — — — — — — — — — —

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-9989

— — — — — — — — — — FOLD HERE — — — — — — — — — —